

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

CASSETTE PART NUMBER	DESCRIPTION
FHCX0-12-10AS	12 FIBER LC - OM3 OPTIMIZED LOSS, POLARITY INDICATOR METHOD AS
FHCZO-12-10AS	12 FIBER LC - OM4 OPTIMIZED LOSS, POLARITY INDICATOR METHOD AS
FHCX0-12-10AF	12 FIBER LC - OM3 OPTIMIZED LOSS, POLARITY INDICATOR METHOD AF
FHCZO-12-10AF	12 FIBER LC - OM4 OPTIMIZED LOSS, POLARITY INDICATOR METHOD AF
FHCXO-12-10BN	12 FIBER LC - OM3 OPTIMIZED LOSS, POLARITY INDICATOR METHOD B
FHCZO-12-10BN	12 FIBER LC - OM4 OPTIMIZED LOSS, POLARITY INDICATOR METHOD B
FHCZA-12-10AS	12 FIBER LC - OM4 ULTRA LOW LOSS, POLARITY INDICATOR METHOD AS
FHCZA-12-10AF	12 FIBER LC - OM4 ULTRA LOW LOSS, POLARITY INDICATOR METHOD AF
FHCZA-12-10BN	12 FIBER LC - OM4 ULTRA LOW LOSS, POLARITY INDICATOR METHOD B
FHC9N-12-10AS	12 FIBER LC - OS2 STANDARD LOSS, POLARITY INDICATOR METHOD AS
FHC9N-12-10AF	12 FIBER LC - OS2 STANDARD LOSS, POLARITY INDICATOR METHOD AF
FHC9N-12-10BN	12 FIBER LC - OS2 STANDARD LOSS, POLARITY INDICATOR METHOD B

								HD FLEX 12 FIBER LC- MPO		
A								CASSETTE	A	
								CUSTOMER DRAWING		
								12F 187HA/00 DATASET FILE NAME 12F 187HA DC/00B		
								12/18/1/_BC/00B		
04/14								UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]		
								.x ± .1 [2.54] .xxx ± .005 [.127] .xx ± .01 [.25] ANGLES ± 5 °		
	00	01-22-15	SAT	JESA	RAR	RELEASED TO PRODUCTION	12F187HA-DC	THIRD ANGLE PROJECTION 12F187HA-DC		
D10100	REV	DATE	BY	СНК	APR	DESCRIPTION	ECN	DRAWN BY DATE CHK SCALE SAT 01-22-15 JESA NONE SHT 2 OF 2		
_							A			